

DECLARATION OF PERFORMANCE

PFPO8EN003

1. Unique identification code of the product-type:


JUTAFOL N 170 AL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See item 1. (stated on packaging and printing of the product)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Vapour barrier manufactured as multilayer polyethylene sheet reinforced with a tear-resistant mesh with heat reflexive aluminized surface to be used against vapour and moisture penetration in pitched or flat roof construction, vertical wall construction or in ceiling. All overlaps should be sealed with recommended special sealing tape.
This product does not contain any dangerous substances.



4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Juta a.s., Dukelská 417, 544 15 Dv r Králové nad Labem, Czech Republic
Tel.: +420 499 314 211, Fax: +420 499 314 210
www.juta.cz

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not listed

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP system 3

7. Declaration of performance concerning a construction product covered by a harmonised standard:

EN 13984, attestation under AVPC system 3 performed and test report issued in CSI a.s.

8. Declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not issued

9. Declared performance:

Essential characteristics	Performance			Harmonised technical specification
	Units	Nominal value	Tolerance	
Reaction to fire	[class]	E	-	EN 13501-1 EN 11925-2
Water tightness	[class]	conforming	-	EN 1928
Water vapour transmission properties (Sd)	[class]	>300	-	EN 1931
Determination of resistance to impact	-	npd	-	EN 12691
Joint strength	[N]	npd	-	EN 12317-2
Maximum tensile force MD/CMD	[N/50mm]	>230 / >170	-	EN 12311-2 EN 13859-1
Resistance to tearing MD/CMD	[N]	>100 / >120	-	EN 12310-2 EN 13859-1
Resistance to alkali	-	npd	-	EN 13984 EN 12311-2
Durability of water vapour resistance against ageing	-	conforming	-	EN 1296 EN 1931

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

This product does not contain any dangerous substances (according to REACH No. 1907/2006).

Signed for and on behalf of the manufacturer by:

Ing. Jiří Hlavatý
Chairman of the board



In Dvůr Králové nad Labem, 01.01.2013