

# TECHNICAL SHEET

valid from 1.6.2013

review .....

<b>PRODUCT NAME:</b>	<b>GREENVILLE 15/140</b>
<b>APPLICATION:</b>	<b>LANDSCAPING</b>
<b>MATERIAL:</b>	<b>PILE:</b> PE monofilament – mild lens profil (straight + texturized)
	<b>PRIM. BACKING:</b> 100% PP
	<b>SECONDARY BACKING:</b> SBR Latex
<b>GAUGE:</b>	3/8"
<b>COLOR:</b>	bicolor green (dark green/light green + field green)

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	15.000/16	± 5%
Pile width	[mm]	0,9	± 10%
Pile thickness	[µm]	170	± 10%
Pile weight per unit area	[g/m <sup>2</sup> ]	870	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	14	± 1
Number of tufts / m <sup>2</sup>	[-/m <sup>2</sup> ]	14.698	± 5%
Number of piles / m <sup>2</sup>	[-/m <sup>2</sup> ]	470.336	± 5%
Pile height	[mm]	15	± 10%
Weight primary backing	[g/m <sup>2</sup> ]	172	± 10%
Weight secondary backing	[g/m <sup>2</sup> ]	700	± 10%
Total weight	[g/m <sup>2</sup> ]	1.742	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,00	± 0,02

## COMMENTS:

**Recommended infill:** non filled

In case of free installation without mechanical fixing or bonding may the turf due to climatic changes shrink up to 1%.

Any supplementary information and certificates are available upon request at our sales department. According to the Directive 76/769 this product does not contain any dangerous substances.

JUTA a.s. reserves the right to technically amended the product mentioned above. Delivered product can slightly differ from these data. JUTA a.s. guarantees the technically quality of the product



JUTA a.s., Dukelská 417  
Dvůr Králové nad Labem  
544 15  
Česká republika  
www.juta.cz

www.jutagrass.com

JUTAgrass, Na Borkách 89  
Dvůr Králové nad Labem  
Tel.: +420 499 314 567  
Fax: +420 499 314 572  
e-mail: [jutagrass@juta.cz](mailto:jutagrass@juta.cz)