

TECHNICAL SHEET

valid from 1.12.2011

review 1.4.2013

PRODUCT NAME:	SCENIC SPRING		
APPLICATION:	LANDSCAPING		
MATERIAL:	PILE:	PE monofilament – lens profil (straight + texturized)	
	PRIM. BACKING:	100% PP	
	SECONDARY BACKING:	SBR Latex	
GAUGE:	3/8"		
COLOR:	bicolor green (field green/spring green + olive green/sand)		

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	13.200/16	± 5%
Pile width	[mm]	0,9	± 10%
Pile thickness	[µm]	170	± 10%
Pile weight per unit area	[g/m ²]	1.943	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	18	± 1
Number of tufts / m ²	[-/m ²]	18.898	± 5%
Number of piles / m ²	[-/m ²]	604.736	± 5%
Pile height	[mm]	35	± 10%
Weight primary backing	[g/m ²]	172	± 10%
Weight secondary backing	[g/m ²]	700	± 10%
Total weight	[g/m ²]	2.815	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,00; 2,00	± 0,02

COMMENTS:

Recommended infill: non filled

In case of free installation without mechanical fixing or bonding may the turf due to climatic changes shrink up to 1%.

Any supplementary information and certificates are available upon request at our sales department. According to the Directive 76/ 769 this product does not contain any dangerous substances.

JUTA a.s. reserves the right to technically amended the product mentioned above. Delivered product can slightly differ from these data. JUTA a.s. guarantees the technically quality of the product.



JUTA a.s., Dukelská 417
Dvůr Králové nad Labem
544 15
Česká republika
www.juta.cz

www.jutagrass.com

JUTAggrass, Na Borkách 89
Dvůr Králové nad Labem
Tel.: +420 499 314 567
Fax: +420 499 314 572
e-mail: jutagrass@juta.cz